

COLOSSEUM Range

Floodlights for large-scale systems



Die-cast aluminium floodlight for discharge lamps of 2000 W maximum power.








- 7 different optics;
- IP66 protection class;
- Vent device to compensate for the internal pressure and avoid the occurrence of condensation;
- Light-protection visor to reduce light emissions;
- Hot-Restrike versions available.

COLOSSEUM RANGE

FLOODLIGHTS FOR LARGE-SCALE SYSTEMS



COLOSSEUM RANGE

COLOSSEUM										
Power (W)	Lamp type	Lamp current (A)	Lamp holder	OPTICS						
										
				Diffused Symmetrical	Restricted Symmetrical	Diffused Asymmetrical	Restricted Asymmetrical	Restricted Circular	Medium Circular	Diffused Circular
600	ST	6.2	E40	GW 84 646		GW 84 658				
1000		10.3	E40	GW 84 647	GW 84 747	GW 84 659	GW 84 759			
1000	MT	9.5	E40	GW 84 647	GW 84 747	GW 84 659	GW 84 759			
1000	MT*	8.25	E40	GW 84 648	GW 84 748	GW 84 660	GW 84 760			
1000	MN	9.5	X528/Cable	GW 84 649	GW 84 749					
1000		9.6	Cable					GW 84 656	GW 84 754	GW 84 756
2000		10.3	X528/Cable	GW 84 644	GW 84 744					
2000		11.3	Cable					GW 84 657	GW 84 755	GW 84 757
2000**		11.3	Cable					GW 84 761	GW 84 766	GW 84 771
MAX.1000				E40	GW 84 693	GW 84 695	GW 84 694	GW 84 696		

* Lamp with 0.7 ÷ 1 kV striking voltage.

** Wiring for hot restrike