

# 68 ACS Range

Distribution board system for ACS construction sites



A construction site distribution board system to meet any installation requirement.

- High impact and UV ray resistance;
- Circuit protection through modular circuit breakers;
- Customised, wired and certified versions.

# 68 ACS RANGE

DISTRIBUTION BOARD SYSTEM FOR ACS CONSTRUCTION SITES



QP



## SWITCHES

Code	CIRCUIT BREAKER	RESIDUAL CURRENT DEVICE
GW 68 521	MTHP 125A 4P TYPE C 16KA	125A 4P TYPE A ADJUSTABLE
GW 68 526	MTS 160A 4P TYPE B 16KA	160A 4P SIDE BY SIDE, ADJUSTABLE
GW 68 531	MTS 250A 4P TYPE N 36KA	250A 4P SIDE BY SIDE, ADJUSTABLE

Q-BOX 4



## NO. INTERLOCKED SWITCHED SOCKET-OUTLETS

## MAIN SWITCH

Code	16A			32A			Magneto-thermal		Isolator		BOARD SUPPLY
	2P+ $\pm$	3P+ $\pm$	3P+N+ $\pm$	2P+ $\pm$	3P+ $\pm$	3P+N+ $\pm$	No. poles	In (A)	No. poles	In (A)	
GW 68 481	3	1							4	40	Appliance inlet
GW 68 482	2	2							4	40	
GW 68 483	2	2			1				4	63	
GW 68 484	2	1	1			1	4	63			
GW 68 511	3			1			2	63			Terminal block
GW 68 512	2	3							4	63	
GW 68 513	2	2			1				4	80	
GW 68 514	2	1	1			1			4	80	

Q-BOX 6



## NO. INTERLOCKED SWITCHED SOCKET-OUTLETS

## MAIN SWITCH


Code	16A			32A			Magneto-thermal		Isolator		BOARD SUPPLY
	2P+ $\pm$	3P+ $\pm$	3P+N+ $\pm$	3P+ $\pm$	3P+N+ $\pm$	3P+N+ $\pm$	No. poles	In (A)	No. poles	In (A)	
GW 68 473	3	3							4	40	Appliance inlet
GW 68 471	3	2		1					4	63	
GW 68 472	2	3		1					4	63	
GW 68 474	2		2		2				4	63	
GW 68 491	2		2		2		4	80			Terminal block
GW 68 494	2	2		2			4	80			
GW 68 492	2	1	1	1	1				4	80	
GW 68 493	3	2		1					4	80	
GW 68 495	2	1			3		4	100			
GW 68 496	3				2	1	4	100			
GW 68 497	2				2	2	4	100			


# 68 ACS RANGE


DISTRIBUTION BOARD SYSTEM FOR ACS CONSTRUCTION SITES



68 ACS RANGE

Q-DIN 	NO. IEC 309 SOCKET-OUTLETS							Nr. DOMESTIC SOCKET-OUTLETS	Nr. SELV 24V SOCKET-OUTLETS	MAIN PROTECTION		BOARD TYPE
	16A		32A	10/16A German standard	16A 2P	MAIN PROTECTION						
	2P+ $\pm$	3P+ $\pm$	3P+ $\pm$			No. poles	In (A)					
GW 68 217	3					2P	16			Portable		
GW 68 203	2				2	2P	16					
GW 68 204	2	2				4P	16					
GW 68 216	4					2P	16					
GW 68 401	2	1			1	4P	16	With metal support				
GW 68 412						2P	16					
GW 68 411	2	2			2	4P	25	With metal wheel support, revolving drum				
GW 68 421	3	2	1		2	4P	40					
GW 68 422	3	1				4P	40					
GW 68 423	2	2				4P	40					
GW 68 424	2	1	1			4P	40					

Q-MC 	NO. IEC 309 SOCKET-OUTLETS				MAIN PROTECTION		EMERGENCY BUTTON	POWER SUPPLY PLUG	IP RATING	BOARD TYPE
	16A		32A	3P+N+E	No. poles	In (A)				
	2P+E	3P+E	3P+N+E							
GW 68 881A	7				4	40A	YES	3P+N+E 32A	56	PORTABLE
GW 68 882A	4	1	2		4	50A		3P+N+E 63A		
GW 68 883A	4	1	1	1	4	50A		3P+N+E 63A		
GW 68 884A	3	1	2	1	4	50A		3P+N+E 63A		

COMBIBLOC 	NO. IEC 309 SOCKET-OUTLETS				MAIN PROTECTION		POWER SUPPLY PLUG	IP RATING	BOARD TYPE
	16A		32A	3P+N+E	No. poles	In (A)			
	2P+E	3P+E	3P+N+E						
GW 66 386	2				2	40	2P+E 32A	55	PORTABLE
GW 66 387	1		1		4	40	3P+N+E 32A		
GW 66 388	2		1		4	40	3P+N+E 32A		
GW 66 389	1		1	1	4	40	3P+N+E 32A		